

## Breathing resistance measuring equipment

### Description:

The basic system comprises a bench mounted air mover (blower / sucker) which is connected by means of flexible PVC tubing, via a regulating valve and variable orifice flowmeter, to the filter to be tested.

A manometer is connected upstream of the filter, in order to measure the pressure drop of the filter, relative to atmosphere, at various air flow rates

For EN 149, the standard specifies that the facepiece is fitted to a Sheffield head. A fixture may be provided in addition to, or instead of, the Sheffield head (please specify). If a fixture is required, please supply specimen facepiece(s) in order for us to manufacture the fixture adaptor(s).

For EN 14387/143, a filter holder will be designed to accept "cartridge" type filters of your design. Please supply specimen filter(s) in order for us to manufacture the filter holder(s).

### Services required:

Bench mounted  
110/230 volts AC, 50/60Hz, mains electricity



*Continued on page 2*

## **Breathing resistance measuring equipment (continued)**

### ***Approximate packed size & weight:***

75 x 50 x 50 cm : 20 kg

### ***Relevant standards:***

EN 140 (requires additional Sheffield Headform)  
EN 143, EN14387 (as supplied)  
EN 149 (requires additional Sheffield Headform & PVC tape)  
EN 405 (requires additional Sheffield Headform)  
EN 1827 (requires additional Sheffield Headform)  
EN 13274-3 method 1